

# MT111

- Classic E3/L3 tread pattern
- Fine tuned for enhanced stability, lifetime, smooth running.
- Wear and Cut resistant compounds
- Suitable for Loader and dumper applications
- Reinforced scuff bands for improved sidewall protection
- Conforms to the latest standards of ETRTO (European Tyre and Rim Technical Organization) and the TRA (Tire and Rim Association)



| Size    | Type | Rating | Rim       | TRA Code | Load Index | Speed Symbol | Tread Depth | Overall Diameter | Section Width | Inflation Pressure | Loading Capacity | Speed (Km/h) |     |       |      |    |
|---------|------|--------|-----------|----------|------------|--------------|-------------|------------------|---------------|--------------------|------------------|--------------|-----|-------|------|----|
| 17.5R25 | T/L  | **     | 14.00/1.5 | E3       | 167B       |              | mm          | 27               | 1347          | 449                | kPa              | 525          | Kg  | 5450  | Km/h | 50 |
|         |      |        |           |          |            |              | in.         | 34/32            | 53.03         | 17.68              | psi              | 76           | lbs | 12000 | mph  | 30 |
|         |      |        |           | L3       | 182A2      |              | mm          | 27               | 1347          | 449                | kPa              | 650          | Kg  | 8500  | Km/h | 10 |
|         |      |        |           |          |            |              | in.         | 34/32            | 53.03         | 17.69              | psi              | 94           | lbs | 18700 | mph  | 5  |
| 20.5R25 | T/L  | **     | 17.00/2.0 | E3       | 177B       |              | mm          | 31               | 1482          | 533                | kPa              | 525          | Kg  | 7300  | Km/h | 50 |
|         |      |        |           |          |            |              | in.         | 39/32            | 58.35         | 20.98              | psi              | 76           | lbs | 16100 | mph  | 30 |
|         |      |        |           | L3       | 193A2      |              | mm          | 31               | 1482          | 533                | kPa              | 650          | Kg  | 11500 | Km/h | 10 |
|         |      |        |           |          |            |              | in.         | 39/32            | 58.35         | 20.98              | psi              | 94           | lbs | 25400 | mph  | 5  |
| 23.5R25 | T/L  | **     | 19.50/2.5 | E3       | 185B       |              | mm          | 41               | 1602          | 607                | kPa              | 525          | Kg  | 9250  | Km/h | 50 |
|         |      |        |           |          |            |              | in.         | 52/32            | 63.07         | 23.90              | psi              | 76           | lbs | 20400 | mph  | 30 |
|         |      |        |           | L3       | 201A2      |              | mm          | 41               | 1602          | 607                | kPa              | 650          | Kg  | 14500 | Km/h | 10 |
|         |      |        |           |          |            |              | in.         | 52/32            | 63.07         | 23.90              | psi              | 94           | lbs | 32000 | mph  | 5  |
| 26.5R25 | T/L  | **     | 22.00/3.0 | E3       | 193B       |              | mm          | 38               | 1735          | 686                | kPa              | 525          | Kg  | 11500 | Km/h | 50 |
|         |      |        |           |          |            |              | in.         | 48/32            | 68.31         | 27.01              | psi              | 76           | lbs | 25400 | mph  | 30 |
|         |      |        |           | L3       | 209A2      |              | mm          | 38               | 1735          | 690                | kPa              | 650          | Kg  | 18500 | Km/h | 10 |
|         |      |        |           |          |            |              | in.         | 48/32            | 68.31         | 27.17              | psi              | 94           | lbs | 40800 | mph  | 5  |
| 29.5R25 | T/L  | **     | 25.00/3.5 | E3       | 200B       |              | mm          | 42               | 1860          | 769                | kPa              | 525          | Kg  | 14000 | Km/h | 50 |
|         |      |        |           |          |            |              | in.         | 53/32            | 73.23         | 30.28              | psi              | 76           | lbs | 30900 | mph  | 30 |
|         |      |        |           | L3       | 216A2      |              | mm          | 42               | 1860          | 769                | kPa              | 650          | Kg  | 22400 | Km/h | 10 |
|         |      |        |           |          |            |              | in.         | 53/32            | 73.23         | 30.28              | psi              | 94           | lbs | 49400 | mph  | 5  |